

DESCRIPTION:

This document describes Aplus 128M x 72-bit 1GB PC133 CL3 SDRAM (Synchronous DRAM) Registered ECC memory module. The components on this module include eighteen stacked 128M x 4-bit (thirty-six 64M x 4-bit) PC133 SDRAM. This 168-pin DIMM uses gold contact fingers and requires +3.3V. The electrical and mechanical specifications are as follows:

FEATURES:

- Single 3.3V $\pm$ 0.3V power supply
- Burst mode operation
- Auto & self refresh capability
- LVTTTL compatible inputs and outputs
- MRS cycle with address key programs
- Latency (Access from column address)
- Burst length (1,2,4,8 & Full page)
- Data scramble (sequential & interleave)
- All inputs are sampled at the positive going edge of the system clock
- Timing Reference: CL-tRCD-tRP (3-3-3)
- Serial presence detect with EEPROM

PERFORMANCE:

CLK cycle time (tCC)	7.5ns (min.) /1000ns (max.)
CLK to output (tSAC)	5.4ns
Row active time (tRAS)	45ns (min.) /100ns (max.)
Row cycle time (tRC)	65ns (min.)
Power Dissipation	18W
Operating Temperature	0°C to 70 °C
Storage Temperature	-55 °C to +150 °C

